

# ARB AIR LOCKER *Air Operated Locking Differentials*

## **RD93** Chrysler 8.25",29 SPL

### Specs:


Axle Spline	29 tooth, Ø30.7mm [1.21"]
Ratio Supported	All
Ring Gear ID	130.5mm [5.14"]
Ring Gear OD	210mm [8.25"]
Ring Gear Bolts	10 bolts on Ø153 mm [6.00"]
Ring Gear Torque	76Nm [55 ft-lb]
Backlash	0.15-0.25mm [0.006-0.010"]
Bearing Cap Torque	81Nm [60 ft-lb]

ITEM #	QTY	DESCRIPTION	PART #	NOTES
1	1	SEAL HOUSING ASSEMBLY	081501	
2	1	CLUTCH GEAR	050801	
3	3	PINION THRUST WASHER	151110	
4	3	PINION GEAR	SEE NOTE	3
5	1	LONG CROSS SHAFT	060204	
6	1	SHORT CROSS SHAFT	060403	
7	1	DIFFERENTIAL CASE	013002	
8	2	COUNTERSUNK SCREW	200213	
9	2	CROSS SHAFT RETAINING PIN	120601	
10	1	TAPERED ROLLER BEARING	160109	2
11	2	SEAL HOUSING O-RING	160227	1
12	1	FLANGE CAP ASSEMBLY	028402	
13	1	BONDED SEAL	160702	
14	8	RETURN SPRING	150107	
15	1	SPLINED SIDE GEAR	SEE NOTE	3
16	1	SPIDER BLOCK	070301	
17	1	SIDE GEAR	SEE NOTE	3
18	2	SIDE GEAR THRUST WASHER	151010	
19	1	TAPERED ROLLER BEARING	NOT SUPPLIED	
*	1	C-CLIP KIT	CCK005	
*	1	AIR LINE (5mm DIA X 6m LONG)	170301	
*	1	BULKHEAD FITTING KIT (O-RING TYPE)	170111	
*	1	PUSH-IN FITTING (5mm to 1/8"BSPP)	170201	
*	1	SOLENOID VALVE (12V)	180103	
*	10	CABLE TIE	180301	
*	1	NIPPLE (1/8" to 1/8" BSPT)	170501	
*	1	SWITCH	180209	
*	1	SWITCH COVER (REAR)	180211	
*	1	BUMPER STICKER	210102	
*	1	WARNING STICKER	210101	
*	1	OPERATING & SERVICE MANUAL	210200	
*	1	INSTALLATION GUIDE	210293	

### Notes:

- For replacement O-rings use only BS138 Viton 75.
- For replacement bearing use Timken part # LM102949 / LM102910.  
  
RD93 suits C-clip & non C-clip applications.  
  
Suitable for use with ABS tone ring.  
  
Ring gear bolts are 3/8" - 20 left-hand thread, and must be removed in a clockwise direction.  
  
Seal housing comes pre-installed.  
To service O-rings or bearing remove the seal housing assembly with a bearing puller.
- Available only as complete 5 gear set #728H021C

\* Not illustrated in exploded view.



# RD93

