

ARB AIR LOCKER *Air Operated Locking Differentials*

RD219 T6 Ranger/BT50, FR, 29 SPL

Specs:


Axle Spline	29 tooth, Ø31.5mm [1.24"]
Ratio Supported	All
Ring Gear ID	121.3mm [4.77"]
Ring Gear OD	190mm [7.48"]
Ring Gear Bolts	10 bolts on Ø145.5mm [5.72"]
Ring Gear Torque	135Nm [100 ft-lb]
Backlash	0.35-0.45mm [0.013-0.017"] (measured off pinion)

Notes:

- 1 For replacement O-rings use only BS136 Viton 75.
- 2 Available only as complete 6 gear set # 728J101
- 3 This differential uses 2 different sized carrier bearings – Timken 32010X (ARB #160116) on the Flange Cap side, and Timken LM603049-LM603011 (ARB #160104) on the Case side.

ITEM #	QTY	DESCRIPTION	PART #	NOTES
01	1	BONDED SEAL	160701	
02	1	CLUTCH GEAR	050802	
03	4	PINION THRUST WASHER	150112	
04	4	PINION GEAR	SEE NOTE	2
05	1	LONG CROSS SHAFT	061302	
06	2	SHORT CROSS SHAFT	061402	
07	1	SIDE GEAR	SEE NOTE	2
08	1	DIFFERENTIAL CASE	013121	
09	2	COUNTERSUNK SCREW	200213	
10	3	RETAINING PIN	120601	
11	1	OE MASTER SHIM	NOT SUPPLIED	
12	1	SHIM KIT	SHK008	
13	1	SEAL HOUSING ASSEMBLY	081824	
14	2	O-RINGS	160207	1
15	2	TAPERED ROLLER BEARING	NOT SUPPLIED	3
16	1	FLANGE CAP	028520	
17	8	RETURN SPRING	150113	
18	2	SIDE GEAR THRUST WASHER	150111	
19	1	SPLINED SIDE GEAR	SEE NOTE	2
20	1	SPIDER BLOCK	070503	
*	1	BULKHEAD KIT	170111	
*	1	PUSH-IN FITTING (5mm to 1/8"BSPP)	170201	
*	1	AIR LINE (5mm DIA X 6m LONG)	170301	
*	1	SOLENOID VALVE (12V)	180103	
*	1	SWITCH	180209	
*	1	SWITCH COVER (FRONT)	180210	
*	10	CABLE TIE	180301	
*	1	WARNING LABEL	210101	
*	1	BUMPER STICKER	210102	
*	1	OPERATION & SERVICE MANUAL	210200	
*	1	INSTALLATION GUIDE	2102219	

* Not illustrated in exploded view.



RD219

